



**CODE COMPLIANCE PLAN**  
 CR1.1 SCALE: 1/4" = 1'-0"  
 TRUE NORTH  
 PLAN NORTH

BUILDING CODE STUDY		SECTION
1. OCCUPANCY	B	SECT 302
A. REQUIRED SEPARATION - MIXED OCCUPANCY BUILDINGS	N/A	TABLE 508.3.3
B. OPENINGS IN OCCUPANCY SEPARATION WALLS	N/A	SECT 705.8
2. TYPE OF CONSTRUCTION:	V-B	TABLE 503
3. ALLOWABLE AREA PER FLOOR	B = 9,000 SF	TABLE 503
A. FRONTAGE INCREASE	N/A	SECT 506.2
B. AUTOMATIC SPRINKLER SYSTEMS	FULLY SPRINKLERED	SECT 504.2
C. UNLIMITED AREA	N/A	SECT 507
D. ACTUAL AREA:	B = 4,517.5 GSF	
4. HEIGHT: ALLOWABLE	B = 40 FT., 2 STORIES	TABLE 503
A. ACTUAL HEIGHT	B = 15 FT 4 INCHES, 1 STORY	
5. PROJECTIONS ALLOWED	N/A	SECT 704.2
6. FIRE RESISTIVE REQUIREMENTS	V-B	
A. EXTERIOR BEARING WALLS	0 HR.	TABLE 601 & 602
B. INTERIOR BEARING WALLS	0 HR.	TABLE 601
C. EXTERIOR NONBEARING WALLS	0 HR.	TABLE 602
D. STRUCTURAL FRAME	0 HR.	TABLE 601
E. PERMANENT PARTITIONS	0 HR.	TABLE 601
F. SHAFT ENCLOSURES	N/A	SECT 707
G. FLOORS / FLOOR-CEILINGS	0 HR.	TABLE 601
H. ROOF / ROOF-CEILINGS	0 HR.	TABLE 601
I. EXTERIOR DOORS & WINDOWS	0 HR.	SECT 715
J. STAIRWAY CONSTRUCTION	0 HR.	SECT 1020
K. WINDOWLESS STORIES	SPRINKLERING NOT REQUIRED IF ONE OPENING MIN. PER 50 L.F. ONE SIDE AND 75 MAX. DISTANCE OPPOSITE WALL	SECT 9.3.2.10.1, 9.3.2.10.2
7. OPENINGS IN EXTERIOR WALLS		TABLE 602 & SECT 704, 715
A. NOT PERMITTED LESS THAN:	N/A	SECT 704.8.2
B. PROTECTED LESS THAN:	N/A	
8. OCCUPANT LOAD	B = 42, (30 BY 1004.4.4 EXC.)	SECT 1002.1, TABLE 1004.1.1
9. EXIT ACCESS		TABLE 1019.1
A. NUMBER OF EXITS	2	TABLE 1019.1
B. WIDTH OF EXITS	36" MIN. STAIR (1009.1 EXC. 1) OTHER EGRESS = 0.2' PER OCCUPANT	SECT 1005.1 & TABLE 1005.1
C. ARRANGEMENT OF EXITS	SEPARATE MIN 1/3 DIA DISTANCE	SECT 1015.2
D. DISTANCE TO EXITS	OCCUPANCY B = 200 FT	SECT 1016 & TABLE 1016.1
10. CORRIDORS		SECT 1017
A. RATING	N/A	TABLE 1017.1
B. WIDTH	36" MIN. (1017.2, EXC. 2)	SECT 1017.2
C. DOORS	N/A	TABLE 715.4
D. WINDOWS	N/A	TABLE 715.4
11. STAIRWAYS		SECT 1009
A. RISE / RUN	RISE = 4-7 INCHES; RUN = MIN 11 INCHES	SECT 1009.3
B. HEADROOM	80 INCHES MIN.	SECT 1009.2
C. ENCLOSURES	N/A	SECT 1020
D. WIDTH	36" MIN. (1009.1 EXC. 1)	SECT 1009.1 & TABLE 1005.1

**LEGEND**

ADMINISTRATION — AREA OCCUPANCY  
 1496 — SQUARE FOOTAGE

**GENERAL NOTES**

1. FIELD COORDINATE LOCATIONS OF WALL CABINET FIRE EXTINGUISHERS WITH THE FIRE MARSHALL. INSTALL PER DETAIL 4 ON SHEET A2.1 TYPICAL.

**GOVERNING CODES**

CONSTRUCTION: INTERNATIONAL BUILDING CODE 2006 EDITION  
 HVAC: INTERNATIONAL MECHANICAL CODE 2006 EDITION  
 PLUMBING: NATIONAL PLUMBING CODE 2006 EDITION  
 ELECTRICAL: NATIONAL ELECTRICAL CODE 2005 EDITION  
 FIRE: INTERNATIONAL FIRE CODE 2006 EDITION  
 HANDICAP: ADA ACCESSIBILITY GUIDELINES/ ANSI STANDARDS  
 EXISTING BUILDING: INTERNATIONAL EXISTING BUILDING CODE 2006 EDITION

**GOVERNING AGENCIES**

CITY OF GREEN RIVER, WYOMING  
 STATE OF WYOMING FIRE MARSHALL

**OCCUPANT LOAD**

(2006 IBC TABLE 1004.1.1)  
 TOTAL OCCUPANT LOAD = 42

**RECORD DRAWINGS**  
 ITEMS INDICATED WITH THIS IS INFORMATION PROVIDED BY THE CONTRACTOR TO THE ARCHITECT AS RECORD INFORMATION AS CONSTRUCTED THE ARCHITECT MAKES NO WARRANTY AS TO THE ACCURACY OF THIS INFORMATION.  
 PLAN ONE/ARCHITECTS

**RENOVATIONS AND REMODEL**  
**SWEETWATER COUNTY JUVENILE PROBATION**  
**Plan one / architects**  
 ~ Cody, Wyoming, 1001 12th St., 82414 (307) 587-8646 ~ rock springs, Wyoming, 4020 devar dr., suite a, 82901 (307) 352-2954, ~ driggs, Idaho, 189 north main, suite 112, 83422 (208) 354-8036 ~



The professional services of the architect are undertaken for and are performed in the interest of SWEETWATER COUNTY. No consequential obligation is assumed by the architect for the benefit of any other person involved in the contract.  
 project: 0620  
 date: 07/23/2007  
 revisions: 08/04/2008

**CR1.1**